

DECLARATION OF PERFORMANCE

According to annex III of the regulation (EU) No. 305/2011

No. LK_2608_PLC_BWS

1. Unique identification code of the product-type:

PLC 6.2.1.2 BWS

2. Intended use:

Suspended ceiling kits for use internally in buildings

3. Manufacturer:

Fural Systeme in Metall GmbH; Cumberlandstraße 66; A-4810 Österreich

Tel: +43-7612/74851-0; fural@fural.at, www.fural.com

5. System or systems of assessment and verification of constancy of performance:

System 3

6. a) Harmonised standard:

EN 13964:2014-08

Notified place(s):

VHT GmbH Institut für Leichtbau Trockenbau Hochbau Darmstadt NB 1503

has performed the initial assessment of the **bearing capacity** according to EN 13964:2014-08 and
has documented it in report No. **PB-598-20 I**

PfB GmbH & Co. Prüfzentrum für Bauelemente KG NB 1644

has performed the initial assessment of the **ball-proof** according to DIN 18032-3:2023-12 and
has documented it in report No. **2026-14-0132-K2**


7. Declared performance

Essential characteristics	Declared performance	Harmonised technical specification
Reaction to fire	A1	EN 13964:2014-08
Flexural strength	NPD	
Asbestos	No content	
Formaldehyde	E1	
Other hazardous substances	No content	
Durability	B	
Bearing capacity	See annex 1	EN 13964:2004-08 / DIN 18032-3:2023-12
Ball-proof	Class 1A/ category D1	

The performance of the above product is in conformity with the declared performances. The manufacturer named above is solely responsible for drawing up the declaration of performance in accordance with Regulation (EU) No. 305/2001. Signed for and on behalf of the manufacturer by:

Gmunden, 13.08.2026

ppa. Dirk Freytag
Authorized Signatory



Fural Systeme in Metall GmbH
Cumberlandstraße 66, A-4810 Österreich

EN 13964:2014-08

Suspended ceiling kits for use internally in buildings

Ceiling system: PLC 6.2.1.2 BWS

Dimensions Baffel:	max. length [mm]:	3000	max. width [mm]:	30
Material Baffel:	Aluminium		thickness [mm]:	1,2
Reaction to fire:	A1			
Release of asbestos:	no content			
Release of formaldehyde:	E1			
Content other pollutants:	no content			
Flexural strength:	Class 3/A/2 N			
Durability:	Class B			

Suspension system:	Nonius hanger with Nonius upper part
Variant:	-
Height / dimensions:	> 250 mm
Bearing capacity hanger:	Nonius hanger with Nonius upper part: 552 N
Bearing capacity suspension key:	KRV DZ on C20: 760 N
Bearing capacity system:	lowest value: hanger/cross connector
Material:	Steel
Reaction to fire:	A1
Content other contaminants:	no content
Durability:	Class B